




1000082 | 08.10

Food & Beverage plus – the new standard for the food-industry.

Resistant to all common sour and alkaline cleaning and disinfectants agents. Protected against water with high-pressure and steam-jet cleaning according to IP69K.

Food & Beverage *plus*

Resistant to all common sour and alkaline cleaning and disinfectants agents




Dust and waterproof, protected against water with high-pressure and steam-jet cleaning (IEC 60529)




No hardening, no discolouring by cleaning through detergent-resistant, PVC-free plastics




Heat- and cold-resistantly
Service temperature range
-40°C to +105°C



Flame-adversely cable



As standard, cable terminals converted with wire-end sleeves



ESCHA Bauelemente GmbH
Elberfelder Str. 32 | 58553 Halver
Phone + 49 2353 708 - 800
Fax + 49 2353 708 - 410
Germany

			Poles	Order-number*	Type-designation*
M8x1	Coupling	straight	3	8035188	FB-SKP3-5/S2300
			4	8035867	FB-SKP4-5/S2300
M8x1	Coupling	angled	3	8035868	FB-SWKP3-5/S2300
			4	8035869	FB-SWKP4-5/S2300
M8x1	Plug	straight	3	8035870	FB-SSP3-5/S2300
			4	8035871	FB-SSP4-5/S2300
M8x1	Plug	angled	3	8035872	FB-SWSP3-5/S2300
			4	8035873	FB-SWSP4-5/S2300
M 12x1	Coupling	straight	4	8033664	FB-WAK4-5/S2300
M 12x1	Coupling	angled	4	8033667	FB-WWAK4-5/S2300
M 12x1	Coupling +LED	angled	4	8035643	FB-WWAK4P2-5/S2300
M 12x1	Plug	straight	4	8033670	FB-WAS4-5/S2300
M 12x1	Plug	angled	4	8033673	FB-WWAS4-5/S2300

Flange (PG9- thread)

M 12x1	Flange-coupling with wire	4	8033631	FB-FK4-0,5/S2300
M 12x1	Flange-coupling with soldering contact	4	8033633	FB-FK4-L/S2300
M 12x1	Flange-plug with wire	4	8033632	FB-FS4-0,5/S2300
M 12x1	Flange-plug with soldering contact	4	8033634	FB-FS4-L/S2300

Connecting cables

M8x1	Coupling straight /Plug straight	3	8039697	FB-SKP3-5-FB-SSP3/S2300
M8x1	Coupling straight /Plug straight	4	8039700	FB-SKP4-5-FB-SSP4/S2300
M8x1	Coupling angled /Plug angled	3	8039703	FB-SWKP3-5-FB-SWSP3/S2300
M8x1	Coupling angled /Plug angled	4	8039706	FB-SWKP4-5-FB-SWSP4/S2300
M 12x1	Coupling straight /Coupling straight	4	8033681	FB-WAK4-5-FB-WAK4/S2300
M 12x1	Coupling straight /Plug straight	4	8033677	FB-WAK4-5-FB-WAS4/S2300
M 12x1	Plug straight /Plug straight	4	8033685	FB-WAS4-5-FB-WAS4/S2300
M 12x1	Coupling angled /Coupling angled	4	8033693	FB-WWAK4-5-FB-WWAK4/S2300
M 12x1	Coupling angled /Plug angled	4	8033689	FB-WWAK4-5-FB-WWAS4/S2300
M 12x1	Plug angled /Plug angled	4	8033697	FB-WWAS4-5-FB-WWAS4/S2300

Actuator-/sensor-junction-system, 8-way with homeruncable (cable lengths 15m), stainless-steel housing

M 12x1	I/O-ports 4-poes+ground		8024411	FB-8M12-5P3-15/P00
--------	-------------------------	--	---------	--------------------

* cable length 5m

Connectors are available with a standard cable length of 2m/5m/10m. For flanges, the wire-length is 0.5m. Other cable- and wire-lengths are available upon request.