

The M12^{Nm} with defined torque gives a signal when it is tight. The integrated torque control system ensures that even without a tool the connection is sealed in accordance with the IP67 protection class.

With the M12^{Nm} one of the principal problems with connection technology is solved!

The M12^{Nm} with defined torque

„tight when it rotates freely“

The first connector in the world which gives a signal when it is tight



Dust and waterproof according to IEC60529

IP67

Without using a tool

Tightend and sealed by hand



Safe and industrially usable



As standard, cable terminals converted with wire-end sleeves



ESCHA Bauelemente GmbH
Elberfelder Str. 32 | 58553 Halver
Phone +49 2353 708 - 800
Fax +49 2353 708 - 410
Germany

		poles	Cable-quality	Order-number*	Type-designation*
Coupling	straight	3	PUR halogen-, PVC free	8042729	NM-WAK3-5/S366
		4		8042769	NM-WAK4-5/S366
		5		8042735	NM-WAK5-5/S366
Coupling	angled	3	PUR halogen-, PVC free	8042747	NM-WWAK3-5/S366
		4		8042751	NM-WWAK4-5/S366
		5		8042754	NM-WWAK5-5/S366
Coupling	straight	3	PUR PVC	8042726	NM-WAK3-5/S90
		4		8042720	NM-WAK4-5/S90
		5		8042723	NM-WAK5-5/S90
Coupling	angled	3	PUR PVC	8042738	NM-WWAK3-5/S90
		4		8042741	NM-WWAK4-5/S90
		5		8042744	NM-WWAK5-5/S90
Plug	straight	3	PUR halogen-, PVC free	8042691	NM-WAS3-5/S366
		4		8042695	NM-WAS4-5/S366
		5		8042698	NM-WAS5-5/S366
Plug	angled	3	PUR halogen-, PVC free	8042710	NM-WWAS3-5/S366
		4		8042714	NM-WWAS4-5/S366
		5		8042717	NM-WWAS5-5/S366
Plug	straight	3	PUR PVC	8042685	NM-WAS3-5/S90
		4		8042688	NM-WAS4-5/S90
		5		8042677	NM-WAS5-5/S90
Plug	angled	3	PUR PVC	8042701	NM-WWAS3-5/S90
		4		8042704	NM-WWAS4-5/S90
		5		8042707	NM-WWAS5-5/S90

* cable length 5m
Connectors are available with a standard cable length of 2m/5m/10m.
Other cable- and wire-lengths are available upon request.