

The S12x1 quick-turn connector provides full compatibility for your terminal devices. It replaces the conventional M12 round connector featuring an exceptional time advantage in installation.

S12x1 is a quick and safe connection for your industrial application.

Fits on **anything** called M12

1000110 | 11.10

S12x1
the Quick-Turn

Compatible with **all** M12x1 threads | 85% less installation time



Safe acoustic and haptic locking indication-signal




Dust- and waterproof according to IEC 60529



High cohesion in locked condition



As standard, cable terminals converted with wire-end sleeves



Male and female versions available in various styles and polarities

ESCHA Bauelemente GmbH
Elberfelder Str. 32 | 58553 Halver
Phone +49 2353 708 - 800
Fax +49 2353 708 - 410
Germany

		poles	Cable-quality	Order-number*	Type-designation*
female	straight	3	PUR halogen-, PVC free	8038445	SV-WAK3-5/S366
		4		8038336	SV-WAK4-5/S366
		5		8038446	SV-WAK5-5/S366
female	angled	3	PUR halogen-, PVC free	8038447	SV-WWAK3-5/S366
		4		8038337	SV-WWAK4-5/S366
		5		8038448	SV-WWAK5-5/S366
female+LED	angled	3	PUR halogen-, PVC free	8042037	SV-WWAK3P2-2/S366
female	straight	3	PUR PVC	8038435	SV-WAK3-5/S90
		4		8038436	SV-WAK4-5/S90
		5		8038437	SV-WAK5-5/S90
female	angled	3	PUR PVC	8038438	SV-WWAK3-5/S90
		4		8038449	SV-WWAK4-5/S90
		5		8038439	SV-WWAK5-5/S90
female+LED	angled	3	PUR PVC	8042035	SV-WWAK3P2-2/S90
male	straight	3	PUR halogen-, PVC free	8039453	SV-WAS3-5/S366
		4		8039374	SV-WAS4-5/S366
		5		8039456	SV-WAS5-5/S366
male	angled	3	PUR halogen-, PVC free	8039458	SV-WWAS3-5/S366
		4		8039375	SV-WWAS4-5/S366
		5		8039463	SV-WWAS5-5/S366
male	straight	3	PUR PVC	8039443	SV-WAS3-5/S90
		4		8039376	SV-WAS4-5/S90
		5		8039446	SV-WAS5-5/S90
male	angled	3	PUR PVC	8039448	SV-WWAS3-5/S90
		4		8039377	SV-WWAS4-5/S90
		5		8039451	SV-WWAS5-5/S90
connecting-cables	male straight/ female straight	3	PUR halogen-, PVC free	8039667	SV-WAK3-5-SV-WAS3/S366
		4		8039671	SV-WAK4-5-SV-WAS4/S366
		5		8039674	SV-WAK5-5-SV-WAS5/S366
connecting-cables	male angled/ female angled	3	PUR halogen-, PVC free	8039623	SV-WWAK3-5-SV-WWAS3/S366
		4		8039624	SV-WWAK4-5-SV-WWAS4/S366
		5		8039625	SV-WWAK5-5-SV-WWAS5/S366
connecting-cables	male straight/ female straight	3	PUR PVC	8039592	SV-WAK3-5-SV-WAS3/S90
		4		8039644	SV-WAK4-5-SV-WAS4/S90
		5		8039649	SV-WAK5-5-SV-WAS5/S90
connecting-cables	male angled/ female angled	3	PUR PVC	8039599	SV-WWAK3-5-SV-WWAS3/S90
		4		8039600	SV-WWAK4-5-SV-WWAS4/S90
		5		8039601	SV-WWAK5-5-SV-WWAS5/S90

* cable length 5m

Connectors are available with a standard cable length of 2m/5m/10m.
Other cable- and wire-lengths are available upon request.