

When it gets hot.


No additional protection against high temperatures. Connectivity for high-temperature applications at permanent operating temperatures of -20°C to $+150^{\circ}\text{C}$ and a maximum operating temperature of $+200^{\circ}\text{C}$.



150°C

High temperature-proof connectors

-20°C ... $+150^{\circ}\text{C}$
Permanent operating
temperatures



$+200^{\circ}\text{C}$
Maximum operating
temperature



Protected against dust and
water-jet according to protection
degree IP65 (IEC 60529)

IP65

As standard, cable terminals
converted with wire-end
sleeves



Available in M8x1, M12x1
and Flange enclosure styles with
various polarities



ESCHA Bauelemente GmbH
Elberfelder Str. 32 | 58553 Halver
Phone +49 2353 708 - 800
Fax +49 2353 708 - 410
Germany

			poles	Order-number*	Type-designation*
M8x1	Coupling	straight	3	8036097	HT-SKP3-5/S2430
			4	8036098	HT-SKP4-5/S2430
M8x1	Coupling	angled	3	8036099	HT-SWKP3-5/S2430
			4	8036100	HT-SWKP4-5/S2430
M8x1	Plug	straight	3	8036101	HT-SSP3-5/S2430
			4	8036102	HT-SSP4-5/S2430
M8x1	Plug	angled	3	8036103	HT-SWSP3-5/S2430
			4	8036104	HT-SWSP4-5/S2430
M 12x1	Coupling	straight	3	8036085	HT-WAK3-5/S2430
			4	8036086	HT-WAK4-5/S2430
			5	8036087	HT-WAK4.5-5/S2430
M 12x1	Coupling	angled	3	8036088	HT-WWAK3-5/S2430
			4	8036089	HT-WWAK4-5/S2430
			5	8036090	HT-WWAK4.5-5/S2430
M 12x1	Plug	straight	3	8036091	HT-WAS3-5/S2430
			4	8036092	HT-WAS4-5/S2430
			5	8036093	HT-WAS4.5-5/S2430
M 12x1	Plug	angled	3	8036094	HT-WWAS3-5/S2430
			4	8036095	HT-WWAS4-5/S2430
			5	8036096	HT-WWAS4.5-5/S2430
M 12x1	Flange-coupling		3	8037311	HT-EC-FK3-0,5/16/S2470
			4	8037322	HT-EC-FK4-0,5/16/S2470
			5	8037323	HT-EC-FK4.5-0,5/16/S2470
			8	8037324	HT-EC-FK8-0,5/16/S2470
			12	8037325	HT-EC-FK12-0,5/16/S2470
M 12x1	Flange-plug		3	8037288	HT-EC-FS3-0,5/16/S2470
			4	8037292	HT-EC-FS4-0,5/16/S2470
			5	8037293	HT-EC-FS4.5-0,5/16/S2470
			8	8037294	HT-EC-FS8-0,5/16/S2470
			12	8037295	HT-EC-FS12-0,5/16/S2470

* cable length 5m

Connectors are available with a standard cable length of 2m/5m/10m. For flanges, the wire-length is 0.5m.
Other cable- and wire-lengths are available upon request.